

## tesa 4289 Heavy Duty Tensilised Strapping Tape

### Product Description/ Application:

tesa 4289 is a heavy duty tensilised polypropylene strapping tape with a natural rubber adhesive system.

tesa 4289 features very high tensile strength with low elongation at the same time. The applied product is highly heat and cold resistant and, therefore, suitable for outdoor use.

#### Applications:

Bundling of heavy steel pipes, palletising, end tabbing of light gauge rolled steel and finished metals.

#### **Dimensions:**

Lengths:	66, 330 m
Widths:	19, 25, 50 mm

Other dimensions on enquiry.

# Technical Data: (mean values)

Backing	Colour	Total thickness <sup>1)</sup>	Tensile strength <sup>1)</sup>	Adhesion/ steel 1)	Elongation at break <sup>1)</sup>
PP	yellow	150 μm	420 N/10 mm	5,3 N/10 mm	35 %

<sup>1)</sup> Parameters of the specification

3540-06/98(EU)



tesa self adhesive tapes are used in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each tesa product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that the tesa self-adhesive tape which you envisage using is appropriate for your particular application. The advisory section of our Technical Service Department will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty. The contents of this product information correspond with the current technical level and may change due to further development.



Quality management

## Internal page - Product information

Product name and - number: tesa 4289

Date of	Date of	Subject of Alteration	KST / PM	KST / F&E
Last	Alteration			
Version:				
05/96	06/98	Cancel. Temp. Resist. / Text / Units / Address	3540 Ortin	3230 Forstreuter
02/95	05/96	Specification (elongation, tensile strength, adhesion)	3540 Ortin	3230 Forstreuter
	02/95	New	3540 Ortin	3230 Forstreuter
	11/01	New address	3540	3230 Forstreuter
			Beeckmann	



tesa self adhesive tapes are used in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each tesa product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that the tesa self-adhesive tape which you envisage using is appropriate for your particular application. The advisory section of our Technical Service Department will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty. The contents of this product information correspond with the current technical level and may change due to further development.

 Ident. no:
 DOFB0006
 Version:
 002
 Valid from:
 01.02.99
 Page 2 of 2